Sourcewell
Ground Maintenance, CE, Utility Tractors, Mowers, RTV's - 112624-KBA
Ag Tractors with Related Attachments - 082923-KBA
NJPA Arkansas 4600055337
Nebraska 14777 (OC)
Mississippi 8200067336

KX040-5R3 WEB QUOTE #2956786
Date: 4/3/2026 1:49:24 PM
-- Customer Information --
Grinshpun, Mark
19094
City of Oakland Park
Mark.grinshpun@oaklandparkfl.gov
954-630-4200

Quote Provided By
FLORIDA COAST EQUIPMENT, LLC
Casey Gifford
2695 DAVIE RD
DAVIE, FL 33314
email: cgifford@floridacoasteq.com
phone: 9549161020

-- Standard Features --

Kubota

K Series KX040-5R3

* * * EQUIPMENT IN STANDARD MACHINE * * *

FEATURES

7" LCD color display - standard
Auto Idler
Rubber Track Model
ROPS/OPG (Top Guard, Level I) 4-Post Canopy
Suspension Seat
Kubota 1 Hydraulic Pump Load Sensing System
1 Variable Displacement Pump
All Controls Hydraulic Pilot Controls
Two Operating Pattern Selection System
Accumulator
Digital Control Panel
Attachment Flow Presets, Service Alerts
Standard Front Dozer Blade w/ Float
360 Degree Full Rotation
70 Degree Left, 55 Degree Right Boom Swing
17.2 gpm Adjustable Auxiliary Hydraulics Port 1
Auxiliary Hydraulics Diverter Valve
Thumb Bracket and Relief Valves
Five Second Quick Preheat System
Key Switch Stop System
Half Pitch Rubber Tracks
Self Bleed Fuel System
Auto-Downshift Two Speed Travel System
Swivel Negative Brake
Travel Negative Brake
Third Line

DIMENSIONS AND OPERATING WEIGHT

KX040-5R3, Rubber Tracks, Air Conditioned ROPS/OPG (Top Guard, Level I) Cab, Dozer Blade
Overall Length 16' 8.1"
Overall Width 5' 6.9"
Overall Height 8' 1.8"
Operating Weight 9,855 lbs.*
Ground Clearance 12.9"
* Includes operator's weight, 175 lbs.

ENGINE

D1803 Kubota DI Turbo CRS Tier 4 Diesel Engine
3 Cylinder, 4 Cycle
38.9 Net HP @ 2200 rpm
40.4 Gross HP

OPERATIONAL DIMENSIONS

Max Digging Depth 11' 2.7"
Max Digging Radius @ Ground Level 17' 9"
Max Vertical Digging Depth 7' 4.8"
Max Dumping Height 12' 9.5"

DOZER BLADE DIMENSIONS

Width 66.9"
Height 15.75"
Lift Above Ground 15.17"
Drop Below Ground 15.94"

PERFORMANCE

Digging Force @ Bucket (K7875) 9,535 lbs.
Digging Force @ Dipper Arm 4,112 lbs.
Travel Speed (Low) 1.8 mph
Travel Speed (High) 3.1 mph
Climbing Ability 36% / 20°
Lift Capacity 4,080 lbs.
Over Front
Blade Grounded
2.0 ft. Load Point Height
8.0 ft. Load radius

-- Custom Options --

KX040-5R3 Base Price:	$77,066.00
Selected Kubota Attachments	
(1) 18" QA TRENCHING BUCKET K7874A-18" QA TRENCHING BUCKET	$1,742.00
(1) 24" QA TRENCHING BUCKET K7875A-24" QA TRENCHING BUCKET	$2,087.00
(1) QUICK COUPLER K7870A-QUICK COUPLER	$1,508.00
(1) HYD THUMB KIT K7910A-HYD THUMB KIT	$4,270.00
(1) AT&T TIER 3 TELEMATICS MODEM DCU6770-AT&T TIER 3 TELEMATICS MODEM	$490.00
Total Kubota Attachments:	$10,097.00
Total Attachments:	$10,097.00
Configured Price:	$87,163.00
Sourcewell Discounts:	
Kubota Items:	($20,919.12)
Total Discount:	($20,919.12)
SUBTOTAL:	$66,243.88
2Yr KX040-5R3 Extended Warranty	$2,650.00
Kubota Item Fees:	
Dealer Assembly:	$165.00
Freight Cost:	$793.75
PDI:	$400.00
Total Unit Price:	$70,252.63
Quantity Ordered:	1
Final Sales Price:	$70,252.63

Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting dealer

***All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price.** All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.

© 2018 Kubota Tractor Corporation. All rights reserved.

198.143.41.31